



ShowTrek
ABN 26 585 292 836
9 Dorset Street
Lonsdale SA 5160 Australia
T: +61 8 8382 9398
F: +61 8 8382 3898
contact@showtrek.com

Product Data Sheet

ISSUED: 21 July 2014

ShowTrek Stage Black

Page 1 of 2

Customers need to appreciate that as ShowTrek cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.

USES:

ShowTrek Stage Black Paint is an economical water based paint formulated for painting Theatre interiors and scenery.

SURFACE PREPARATION:

Surfaces to be painted should be dry and free from dew. They should also be clean and free of dust and grease.

APPLICATION:

Stir and mix thoroughly before application. ShowTrek Stage Black Paint can be applied with airless spray equipment, brushed or rolled.

THINNING:

Ready for application

CLEAN UP:

Water.

DRYING:

Half hour under normal conditions, 1-2 hours before re-coat (at 25°C).

COLOUR:

Black

FINISH:

Ultra low sheen

COVERAGE:

Theoretical coverage is 10 m²/Litre at 40 micrometres dry film thickness.

PACK SIZE:

20 litre.

VEHICLE TYPE:

Modified P.V.A. emulsion.

Customers need to appreciate that as ShowTrek cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.

ShowTrek Stage Black

FILM PROPERTIES:

Solvent Resistance	Poor.	Chemical Resistance	Fair.
Abrasion Resistance	Fair.	Impact Resistance	Good.
Heat Resistance	Poor.	Flexibility	Good.

PRECAUTIONS:

Do not apply when the temperature is less than 10°C, above 30°C or above 85% Relative Humidity.

Safety Directions: *KEEP OUT OF REACH OF CHILDREN – DO NOT SWALLOW.* Breathing the concentrated vapour may be harmful and may cause lung irritation. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and gloves when mixing and using. Handling and usage of this product must be carried out under well ventilation conditions that prevent inhalation of vapours, dust or mist. Use the appropriate breathing equipment (refer to Aust Stand. 1716) when ventilation is restricted. Keep containers closed when not in use.

First Aid Instructions: If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, *DO NOT INDUCE VOMITING* drink plenty of water and seek medical advice. Contact a Doctor of Poisons Information Centre (Phone 131126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation occurs seek prompt medical advice. Immerse contaminated clothing in water for 24 hours and do not use until laundered. In case of eye contact, hold eyes open and flood with running water for at least 15 minutes seek medical advice.

Leaks, Spills and Disposal: Contain or shut off leak if safe to do so. For large leaks or spills or spills in poorly ventilated areas, use respiratory protection, protective apparel and footwear. Spills should be absorbed either with rags (small spill) or dry sand/earth (large spill). DO NOT pour left over product down the drain – retain it in marked sealed container for future use or disposal through chemical waste collection programs. Dried empty cans can be recycled and should be disposed of via council steel recycling facilities.

Fire: Product is not flammable. Dried material may burn in a fire and may be treated with normal fire fighting procedures.

Hazard:



The above coloured square is provided for a quick reference as to the hazard level of a product. Blue refers to coatings with low hazard (eg water based wall paints). Yellow refers to medium hazard products such as QD enamels, which contain solvents, are flammable and need respirators for vapour protection. Red refers to products with special hazards such as isocyanate cured two pack finishes.

Fire: Use foam and breathing apparatus. Avoid breathing products of combustion.

Customers need to appreciate that as ShowTrek cannot control the conditions under which our products are used, we therefore are unable to guarantee suitability or accuracy in every situation. If any doubt exists, do check with our technical people. Before large-scale use always test on a small sample and ascertain suitability. No warranties express or implied are made. The risks and liability arising from handling, storage, use and compliance with legal restrictions, rests with the buyer.